GIS Grew From Maps to Intelligence

A white paper



JPR

Jon Peddie Research

Introduction

Computerized GIS did not come from one company or one product. It grew from a rich stew of government land inventories, university mapping software, CAD workstations, utility databases, and professional planning organizations. Roger Tomlinson's CGIS gave the field its foundation. Harvard's SYMAP software proved computer mapping could scale. Intergraph, Synercom, Comarc and ESRIbegan to commercialize GIS software in the early 1980s. Hardware companies like Tektronix, Calcomp, Summagraphics, and Versatec supplied specialized equipment. Their combined work turned maps into spatial databases and, eventually, into today's location-aware analytics platforms for cities, infrastructure, logistics, climate, and AI systems.

Computerized GIS began as a practical answer to a national land-management challenge. Canada needed to classify and analyze rural land across agriculture, forestry, wildlife, recreation, soils, and water resources. Roger Tomlinson, called the "father of GIS," proposed a computer system that could store geographic boundaries, attach descriptive attributes, and run overlay analysis across large map layers. The Canada Geographic Information System, or CGIS, began in 1963 for the Canada Land Inventory and gave the field its core model: geography as data, not just cartography as presentation.

CGIS mattered because it separated spatial data from attribute data. A boundary no longer served only as a line on a map. It could carry soil quality, land capability, crop potential, forestry value, or conservation status. That architecture gave planners a way to ask questions. Which land

© Copyright Jon Peddie Research 2026

classes overlap with certain soil types? Which areas support agriculture? Which regions need management attention? CGIS turned the map into a database interface.

The next phase came from universities, especially the Harvard Laboratory for Computer Graphics and Spatial Analysis. Howard Fisher developed SYMAP, or Synagraphic Mapping System, and brought it to Harvard in 1965. SYMAP generated thematic maps from tabular data using line-printer output, patterns, contours, and shading. It did not offer a modern GIS interface. It gave planners, geographers, and students a working proof that computers could synthesize spatial data and produce crude but useful maps on everyday equipment.



Figure 1. Three varieties of maps created with SYMAP. Lab-Log (1977), published by the Laboratory for Computer Graphics and Spatial Analysis, Graduate School of Design, Harvard University.

© Copyright Jon Peddie Research 2026

SYMAP also created a training path. Harvard distributed the software widely and built a community around computer mapping. Later Harvard work, including SYMVU, POLYVRT, and ODYSSEY, moved closer to integrated spatial analysis and vector data modeling. The lab influenced people who later shaped commercial GIS and computer graphics, including figures connected to ESRI and Intergraph. Harvard did not try to commercialize GIS at modern scale. It gave the industry methods, people, and confidence.

CAD then gave GIS much of its production machinery. Early CAD systems developed for aerospace, architecture, engineering, PCB layout, and plant design supplied interactive graphics, precision coordinate handling, vector editing, layers, snapping, plotting, and digitizing workflows. Those capabilities gave mapping teams tools for creating and maintaining digital geometry. Utilities, city planners, and public works departments could trace parcels, roads, pipes, power lines, and contours into digital systems.



Figure 2. Example of raster and vector data viewed together in CAD. (Source: KYTC)

M&S Computing, later Intergraph, played a central role in that CAD-to-mapping path. M&S and ESRI both began in 1969, though their early business models differed. M&S built interactive graphics systems rooted in engineering and defense work. By 1973, it had developed a mapping system for Nashville that let planners call up city blocks along with population and zoning data. That type of cadastral system showed how CAD-like graphics could support municipal information access.

ESRI followed a different path in its early years. Jack and Laura Dangermond founded Environmental Systems Research Institute in 1969 as a land-use consulting firm. The company grew from planning, environmental analysis, and spatial problem-solving. Its commercial software identity arrived later with ARC/INFO in the early 1980s. ARC handled geographic

© Copyright Jon Peddie Research 2026

input, processing, and output. INFO handled the relational database side. That pairing helped define GIS as a spatial database and analysis platform.

The distinction matters. CAD systems knew how to draw geometry with precision. GIS systems needed to know what geometry meant, how features connected, which polygons shared boundaries, which lines formed networks, and which attributes belonged to each object. Topology and database integration gave GIS its analytic power. CAD contributed geometry. GIS added meaning, spatial relationships, queries, and overlay logic.

Bentley Systems also belongs in the CAD-to-GIS branch. MicroStation grew from the Intergraph IGDS/DGN environment and became a major infrastructure design platform. Intergraph used MicroStation as a platform for MGE and FRAMME, which tied engineering graphics to GIS and AM/FM workflows. After Bentley separated from Intergraph, it developed its own geospatial products, including MicroStation GeoGraphics and later Bentley Map. Bentley's GIS influence centered on infrastructure, transportation, utilities, and engineering workflows, where precise design geometry, asset data, and geospatial context had to live together.

Autodesk added another branch to GIS history by moving location intelligence into the CAD installed base. AutoCAD users already maintained roads, parcels, utility networks, plant layouts, and engineering drawings as digital geometry. AutoCAD Map, released in 1996, gave those users GIS functions without forcing them to abandon CAD workflows. MapGuide then extended Autodesk's role into web mapping, and FDO gave its tools a cleaner way to connect with spatial databases. Autodesk did not originate GIS, yet it helped pull GIS into engineering, infrastructure, and asset management departments that thought in drawings before they thought in geodatabases.

Summagraphics helped solve another problem: getting paper maps into computers. In the 1970s and 1980s, most geographic data lived on paper maps, Mylar sheets, utility plans, engineering drawings, and parcel books. Summagraphics digitizing tablets and tables converted hand-traced positions into X,Y coordinate data. An operator taped a map to a tablet, registered control points, and used a stylus or puck to trace roads, parcels, contours, pipes, and boundaries. That process (however laborious) created vector data for CAD, Automated Mapping/Facilities Management (AM/FM), and GIS systems.

© Copyright Jon Peddie Research 2026

Figure 3. Digitizer systems for GIS and mapping GTCO's Surface-Lit AccuTab Digitizer. (Source: GTCO)

The company's BitPad and related products helped make digitizing practical for municipalities, utilities, engineering firms, and desktop users. Digitizers did not create GIS theory. They supplied the intake valve for spatial data. Without mass digitization, early GIS software would have lacked the data volumes needed for production use.

Synercom Technologies helped define Automated Mapping and Facilities Management, or AM/FM. Its systems served utility, forestry, infrastructure, and photogrammetric mapping markets. Synercom competed with Computervision and M&S/Intergraph in the late 1970s and early 1980s on DEC PDP/VAX platforms and custom graphics workstations. In Indianapolis, Synercom supported IMAGIS base mapping and utility mapping for water, gas, sewer, electric, and telephone systems.

Synercom's contribution came through production workflows. Utilities needed more than maps. They needed asset IDs, maintenance records, circuit information, pipe sizes, service areas, and work histories tied to map features. AM/FM systems gave them a geographic window into facilities databases. That model pushed GIS toward infrastructure management and enterprise asset systems.

ARC/INFO came from ESRI, (Environmental Systems Research Institute) founded by Jack and Laura Dangermond in 1969, but the key technical inventor/designer was Scott Morehouse. ESRI hired Morehouse in 1981 to design and launch ARC/INFO after Morehouse had worked at the

© Copyright Jon Peddie Research 2026

Harvard Laboratory on ODYSSEY, an important vector GIS predecessor. ARC/INFO was released in 1982.

By the late 1970s, GIS had moved past simple drafting toward vector data tied to geographic coordinates. Points and lines had value, but polygons let agencies manage soils, land use, watersheds, jurisdictions, and planning zones as closed objects with attributes. That made the system useful for resource management, not just mapmaking.

Comarc Design Systems, founded in 1976, belongs in GIS history because it offered another early commercial route into the field: polygon-based land and resource information systems. North Carolina's Land Resources Information Service adopted Comarc hardware and software in 1977, after the 1974 North Carolina Land Policy Act created demand for statewide geographic decision support. The state used the system to capture and manage natural and cultural resource data.

North Carolina later moved to ARC/INFO in 1986 and preserved as much Comarc data as possible. That migration shows how early vendors built the spatial databases that later GIS platforms inherited.

Figure 4. The ARC/INFO system for managing geographic information. (Source: ESRI)

© Copyright Jon Peddie Research 2026

URISA helped the growth of a GIS professional network. The Urban and Regional Information Systems Association grew from urban and regional planning information-system conferences in the 1960s. It brought together planners, geographers, computer scientists, cartographers, utilities, census users, local governments, and public administrators. URISA conferences and committees helped practitioners share methods, compare systems, debate accuracy, discuss data structures, and establish GIS as a professional discipline.

This institutional layer mattered because GIS needed users as much as software. Agencies had to justify budgets, define data standards, train staff, build departments, and share information across jurisdictions. URISA gave early GIS a home outside any single vendor. On a related note, the Map Overlay and Statistical System (MOSS), developed by Carl Reed for the US Department of Interior in the late ’70s, was the first open-source, public domain GIS software.

By the 1980s and 1990s, GIS moved from mainframes and specialized workstations toward commercial software running on minicomputers, and eventually, desktop systems. ESRI’s ARC/INFO and ArcView expanded use among planners, utilities, natural-resource agencies, and businesses. Intergraph built major AM/FM and mapping systems. MapInfo brought desktop mapping into business analysis. GRASS GIS (US Army Corps of Engineers) gave government and research users an open-source path.

The web then changed GIS distribution. Google Maps and Google Earth (a commercial version of the government’s Keyhole software) made interactive digital maps accessible to the public. QGIS, PostGIS, cloud databases, satellite imagery platforms, mobile GPS, drones, and IoT sensors expanded the field again. Modern GIS now supports routing, logistics, climate analysis, asset management, emergency response, construction, agriculture, defense, telecom planning, and real-time operations like route selection and GPS tracking.

© Copyright Jon Peddie Research 2026



Figure 5. The layers of GIS.

GIS history shows a layered evolution. CGIS created the database model. SYMAP proved computer mapping. CAD and Intergraph supplied graphics production. Summagraphics enabled data capture. Synercom refined AM/FM. URISA organized the profession. ESRI packaged GIS into a commercial platform. The field matured because each group solved a different bottleneck.

© Copyright Jon Peddie Research 2026

GIS now sits inside enterprise software, cloud analytics, digital twins, mobile apps, autonomous systems, and AI pipelines. Its history explains why location intelligence depends on more than maps. It needs data models, geometry engines, topology, sensors, imagery, databases, standards, and domain knowledge. The next stage will connect GIS with AI models that reason over space, infrastructure, movement, risk, and physical-world context.

Digital twins rely on GIS to move beyond static 3D models and become "living" operational tools. By using location as a common key, GIS integrates disparate datasets—such as sensor telemetry, BIM (building information modeling) files, and business records—into a unified, context-aware environment.

Summary

GIS grew through practical engineering, not a single invention story. CGIS, SYMAP, CAD, digitizers, AM/FM, URISA, Intergraph, Synercom, Summagraphics, and ESRI each solved one constraint. ISVs should treat this history as a platform lesson: Durable markets emerge when data capture, data structure, visualization, analysis, workflows, and professional adoption mature together into repeatable systems.

GIS history forecasts an inflection point in AI as spatial context gives AI systems a physical-world frame of reference. Maps, sensors, CAD models, satellite imagery, and asset databases now feed models that plan routes, inspect infrastructure, manage cities, and simulate risk. The inflection point arrives when AI stops treating location as metadata and starts reasoning over topology, proximity, terrain, networks, time, and constraints as core inputs for decisions.

Cover image

It may sound like science fiction, but it was no joke for Jaguar XJ owner Martin Lindsay, who parked his car near the under-construction building, officially called 20 Fenchurch Street, known by many Londoners as the “Walkie-Talkie” for its distinctive shape.

Had the designers used a GIS system, they would have seen the path of the sun’s reflected light across all seasons and could have recommended preventative measures.

© Copyright Jon Peddie Research 2026

© Copyright Jon Peddie Research 2026. All rights reserved.

Reproduction in whole or in part is prohibited without written permission
from Jon Peddie Research.

This report is the property of Jon Peddie Research (JPR) and made available to a restricted number of clients only upon these terms and conditions.

Agreement not to copy or disclose. This report and all future reports or other materials provided by JPR pursuant to this subscription (collectively, "Reports") are protected by: (i) federal copyright, pursuant to the Copyright Act of 1976; and (ii) the nondisclosure provisions set forth immediately following.

License, exclusive use, and agreement not to disclose. Reports are the trade secret property exclusively of JPR and are made available to a restricted number of clients, for their exclusive use and only upon the following terms and conditions. JPR grants site-wide license to read and utilize the information in the Reports, exclusively to the initial subscriber to the Reports, its subsidiaries, divisions, and employees (collectively, "Subscriber"). The Reports shall, at all times, be treated by Subscriber as proprietary and confidential documents, for internal use only. Subscriber agrees that it will not reproduce for or share any of the material in the Reports ("Material") with any entity or individual other than Subscriber ("Shared Third Party") (collectively, "Share" or "Sharing"), without the advance written permission of JPR.

No material from JPR may be used for AI training. The term "AI training" refers to the process of teaching a machine learning model to make predictions or decisions based on data. That includes but is not limited to: 1. Supervised Learning: Training with labeled data (input-output pairs), such as Image classification, spam detection, sentiment analysis. 2. Unsupervised Learning: Training with unlabeled data to find patterns or groupings, such as Clustering (e.g. K-means), dimensionality reduction (e.g. PCA). 3. Self-Supervised Learning: A hybrid where the system generates labels from the data itself, such as Contrastive learning, masked language modeling (used in GPT, BERT). 4. Reinforcement Learning (RL): Agents learn by taking actions and receiving rewards or penalties, such as Game-playing AIs (e.g. AlphaGo), robotics, navigation. 5. Unsupervised Reinforcement Learning: Agents explore environments without a defined task or reward, such as Pretraining agents for general skills before fine-tuning. 6. Multi-Task Learning: Training one model to handle multiple tasks simultaneously, such as A model that can translate and summarize text. 7. Transfer Learning: Using a pre-trained model on a new, related task with minimal retraining, such as Fine-tuning GPT or BERT on a specific domain. 8. Few-Shot / One-Shot / Zero-Shot Learning, Few-shot: Trained on a very small number of examples. One-shot: Trained on just one example. Zero-shot: Performs tasks without any task-specific training. 9. Meta Learning ("Learning to Learn"): Training models that can adapt to new tasks with very little data, such as Model-Agnostic Meta-Learning (MAML). 10. Curriculum Learning: Training models by gradually increasing task difficulty. 11. Online Learning: Model updates continuously as new data arrives, such as Stock prediction systems. 12. Federated Learning: Training across decentralized devices without sharing raw data, such as Mobile keyboard prediction models. 13. Contrastive Learning: Learns by comparing positive and negative pairs of data. Used In: Self-supervised vision models like SimCLR, CLIP. Specialized AI Training Terms, Fine-tuning: Adjusting a pre-trained model on a new dataset. Pretraining: Initial broad training, usually on large datasets (e.g. GPT pretraining). Prompt Tuning / Instruction Tuning: Adjusting models using instructions or task-specific prompts. RLHF (Reinforcement Learning from Human Feedback): Used in GPT models to align behavior with human intent. Distillation: Training a smaller model to mimic a larger model. Active Learning: Selecting the most informative data points to label next. Semi-supervised Learning: Mix of labeled and unlabeled data for training.

Subscriber shall be liable for any breach of this agreement and shall be subject to cancellation of its subscription to Reports. Without limiting this liability, Subscriber shall be liable for any damages suffered by JPR as a result of any Sharing of any Material, without advance written permission of JPR.

Important Note re Sharing of Material. If Subscriber wishes to Share any Material with any Shared Third Party, it shall contact JPR and request permission to do so. JPR shall forthwith prepare an appropriate Sharing agreement, which shall set forth the name and contact information of the Shared Third Party, the terms and conditions of such Sharing, the compensation to JPR for such Sharing, and the agreement by Subscriber and the Shared Third Party that the Shared Third Party shall not, under any circumstances, Share any of the Material with any other entity or person.

Disclaimers. JPR Reports contain "reviews" of various products and information. The content of these Reports represents the interpretation and analysis of statistics and information that are either generally available to the public or released by entities or individuals deemed responsible. The information in the Reports is believed to be reliable but is not guaranteed as to its accuracy or completeness. The Reports do not endorse or attempt to sell any products and should not be interpreted differently. JPR assumes no responsibility for the correct or incorrect usage of any trademarks or service marks.

© Copyright Jon Peddie Research 2026